

R-LINE[®]

CURVE



5 YEAR
limited
led warranty



Catalog Number Example

RLINS-OPAL-1-BL-27K-C90-48V-010V-700LF-10F-R36A90

A SYSTEM

R-LINE RLINS

I OUTPUT

300 lm/ft. 3w/ft. 300LF - 3WF
700 lm/ft. 7w/ft. 700LF - 7WF

B PRODUCT

Curve Opal OPAL

J DIMENSION

Radius 18"/90° R18A90
Radius 24"/90° R24A90
Radius 36"/90° R36A90

C INSET HEIGHT

1" flush with R1/R3 Track 1
2" Inset available Q1 2024 2

D ADAPTER COLOR

Black BL
White WH
recommendation: adapter & track color should match

Other Options

+ LINEAR OPAL

see R-Line Linear Opal cutsheet

+ LOUVER

see R-Line Louver cutsheet

+ SPOT

see R-Line Spot cutsheet

E CCT/CRI

2700K /CRI>90 27K - C90
3000K /CRI>90 30K - C90
3500K /CRI>90 35K - C90

F VOLTAGE

48V low constant voltage 48V
remote driver required (see driver cutsheet)

G DIMMING

0-10V 1% dimming 010V


H CIRCUIT

1 or 2 Circuit *
compatible with 1 or 2 track(see driver wiring diagram)
*leave empty


CONFIGURATIONS



R1 Track



R2 Track



R3 Track

COLORS



Black



White

BASO
basolighting.com
xalusa.com

DIMENSIONS

