

PERFORMANCE

- 48V low voltage track
- · Multiple inset options available
- CRI > 90+
- Flexible magnetic profile system




MOUNTING

Ceiling





MAGNETIC ATTACHMENT



10 Business Days for all QuickShip items

- Maximum quantity: 400'
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard XAL terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

MLINS1.1-SUR-BL-48V-010V-ST-04FT

A RANGE

M-LINE 1.1 ML I NS 1 . 1
M-LINE 1.2 ML I NS 1 . 2

MOUNTING

Surface mount	SUR
os Pendant	PDT

pendant suspension set includes cable suspension and one white J-box cover

© COLOR outside / inside

■ Black B L

O VOLTAGE

constant voltage track

(3) DIMMING

OS 0-10 V 1% single control 0 1 0 V

G SHAPE / PATTERN

os Linear S T

© DIMENSIONS IN FEET

os Linear 4'	04FT
Linear 8'	08FT
Custom length	XXFT
(QS in 2' increments only)	





s

M-LINE 1.1 channel dimensions

CEILING

PENDANT





Possible shapes top view

please provide RCP to ensure correct shape orientation

LINEAR




Power feeder locations

POWER FEED



LINEAR POWER COUPLER



M-LINE Mounting Instructions

Get access to the M-LINE mounting instructions faster by scanning the QR code.

https://www.xalusa.com/resources/mounting-instructions/m-line

