


PANO 2" WOODWORKS® Grille Tegular 9/16" & 15/16" Integration




5 YEAR
limited
led warranty




PERFORMANCE

- Coordinates with Woodworks® Grille Tegular & integration ceiling panel
- Up to 109lm/W
- High performance opal cover
- Remote mountable LED driver
- Damp rated



WoodWorks® Grille Tegular Ceiling Integration

Grille Tegular Panel



REMOTE MOUNTING

Quick and easy electrical connection

REMOTE MOUNTING



[link to page](#)


ARMSTRONG CEILING TYPES

WARM, AESTHETIC ROOMS

WT5 - WOODWORKS®
GRILLE TEGULAR 15/16"




WT5 - WOODWORKS®
GRILLE TEGULAR-VERTICAL SLATS



WLS - WOODWORKS®
GRILLE SOLID WOOD PANELS



WLV - WOODWORKS® GRILLE
VENEERED PANELS



Catalog Number Example

PANO2-WT9-WH-PS-OP-30K-C80-UNV-010V-0275LF-ST-02FT

A RANGE

PANO 2" PANO 2

H VOLTAGE

120V / 277V UNV

B CEILING TYPE

WoodWorks® Grille WT 9
Tegular 9/16"
WoodWorks® Grille WT 5
Tegular 15/16"

please contact your Armstrong® ceilings rep for the Integrated Light Connection Clip for the specified ceiling type

I DIMMING

0-10V 1% 0 1 0 V
DALI DAL I
Lutron EcoSystem LES 1
Quantum, Vive, GRAFIK Eye,
HomeWorks

Power over ethernet PO E C
consult customer service for compatibility
Custom dimming X X X X
consult customer service for compatibility

C COLOR

White WH
Black BL

J OUTPUT LM/FT

275 lm/ft 100% ↓ 0 2 7 5 L F
425 lm/ft 100% ↓ 0 4 2 5 L F
600 lm/ft 100% ↓ 0 6 0 0 L F

D POWER FEED LENGTH

4' standard integrated P S
10' medium remote option P M
30' long remote option P L

power feed distance denotes secondary wiring from detachable driver box to fixture; driver box comes with a 6ft conduit for primary wiring

K CIRCUIT / EM

Single circuit *
*leave blank

L SHAPE / PATTERN

Linear / straight S T

E LENS

HP opal cover O P

M DIMENSIONS IN FT

2' fixture 0 2 F T
4' fixture 0 4 F T

fixture replaces full length of ceiling panel slats; please see table on next page and fixture length dimensions

F CCT

2700K 2 7 K
3000K 3 0 K
3500K 3 5 K
4000K 4 0 K
Custom CCT X X K

G CRI

CRI > 80 C 8 0
CRI > 90 C 9 0

xalusa.com


Technical data

	SIZE TYPE	LED COLOR TEMPERATURE	INPUT WATTS	DELIVERED LM TOTAL	LIGHT DISTRIBUTION	DELIVERED LUMEN DIRECT	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
PANO 2" e LED	2' opal	40K	4.8 W	550lm	100% down	550lm	70%	108lm/W
	4' opal		9.6 W	1100lm		1100lm		109lm/W
e ² LED	2' opal	40K	7.4 W	850lm	100% down	850lm	70%	115lm/W
	4' opal		14.9 W	1700lm		1700lm		115lm/W
e ²⁺ LED	2' opal	40K	11.3 W	1200lm	100% down	1200lm	70%	108lm/W
	4' opal		22.7 W	2400lm		2400lm		108lm/W

for 27K, 30K or 35K multiply lm value by 0.96

WoodWorks® Grille Tegular Ceiling Integration

(for more ceiling options, please see CEILING OPTIONS pages)



Available lengths for ceiling types

CEILING TYPE	2 FT	4 FT	6 FT	8 FT
WoodWorks® Grille Tegular 9/16	23.375"	47.375"	n/a	n/a
WoodWorks® Grille Tegular 15/16	23"	47"	n/a	n/a
WoodWorks® Grille Classic	23"	47"	71"	95"
WoodWorks® Grille Forte	*23"	47"	71"	95"
WoodWorks® Linear Solid Wood panels	*23"	*47"	*71"	95"
WoodWorks® Linear Veneered panels	*23"	*47"	*71"	95.25"

*Woodworks ceilings are not available in this length. Wood panels need to be cut in the field to fit this length.

INTEGRATED LIGHT CONNECTION CLIP

Armstrong® Ceilings Integrated Light Connection Clip

visit armstrongceilings.com/linearlighting

please contact your Armstrong Ceilings rep


WoodWorks® ceiling systems

XAL PANO is only approved for Armstrong® WoodWorks Grille Tegular 9/16, WoodWorks Grille Tegular 15/16, WoodWorks Grille, WoodWorks Linear Solid Wood panels and WoodWorks Linear Veneered panels ceiling systems. Refer to armstrongceilings.com for installation instructions related to the ceiling products.


DIMENSIONS

PANO 2"


WT9 - ARMSTRONG® WOODWORKS® GRILLE TEGULAR 9/16 PANELS






WT9 view from below



WT5 - ARMSTRONG® WOODWORKS® GRILLE TEGULAR 15/16 PANELS



WT5 view from below



PANO mounting instructions

Get access to the PANO mounting instructions faster by scanning the QR code.

<https://www.xalusa.com/resources/cut-sheets/pano>

